

INDEX OF AUTHORS

VOLUME XLV

TRANSACTIONS OF AMERICAN SOCIETY FOR METALS

1953

A

Allten, A. G. 498
Averbach, B. L. 576

B

Beall, R. A. 862
Beattie, H. J., Jr. 397
Bishop, S. M. 993
Boegehold, A. L. 1056
Bowen, K. W. J. 443
Bruckart, W. L. 286, 314
Bucklin, A. G. 151
Buffum, D. C. 725, 732
Bumps, E. S. 1008

C

Carr, F. L. 725, 732
Channon, S. L. 200
Chapman, R. D. 710
Christenson, A. L. 638
Clark, D. S. 620
Cohen, Morris 576
Craighead, C. M. 286, 314, 941

D

Dorn, J. E. 249, 275
Dulis, E. J. 42
Duwez, Pol 934

E

Eichelman, G. H., Jr. 77

F

Fontana, M. G. 993
Furman, D. E. 429

G

Garofalo, F. 377
Giacobbe, J. B. 134
Gilbert, H. L. 862
Goldberg, A. 275
Goldhoff, R. M. 941

Goldman, Manuel 732
Goss, N. P. 333
Grant, N. J. 105, 151
Grobe, A. H. 475, 1080
Grosse, A. V. 758

H

Hamburg, J. F. 686
Hansen, M. 901, 915, 1008
Hayes, E. T. 893
Hoar, T. P. 443
Houston, E. G. 42
Hu, L. W. 686
Hull, F. C. 77
Hum, J. K. Y. 105

J

Jaffe, L. D. 725, 732
Jaffee, R. I. 286, 314, 941
Jaczak, C. F. 771
Jominy, W. E. 710

K

Kayser, F. X. 1056
Kessler, H. D. 1008
Kirshenbaum, A. D. 758

L

LaChance, M. H. 286, 314
Lane, J. R. 177
Liu, T. S. 677
Lubahn, J. D. 787
Lundin, C. E. 901

M

Malenock, P. R. 377
Marin, Joseph 686
McPherson, D. J. 901, 915
Mehl, R. F. 1080

N

Newkirk, J. B. 1020

P

Paasche, O. G.	893
Paliwoda, E. J.	344
Payson, P.	498
Peretti, E. A.	677
Perkins, F. C.	972

R

Reynolds, M. B.	839
Rhines, F. N.	1029
Roberson, A. H.	893
Roberts, C. S.	576
Roberts, G. A.	475
Rosi, F. D.	972
Rowland, E. S.	638, 771

S

Saunders, M. S.	362
Shahinian, Paul	177
Shaw, H. L.	941
Shaw, R. B.	249
Shepard, L. A.	249
Shoenberger, L. R.	344
Sinnott, M. J.	362

Smith, C. S.	533
Smith, G. V.	42, 377
Snyder, H. J.	605
Spretnak, J. W.	993
Starr, C. D.	249, 275
Stephens, W. W.	862

T

Talbot, A. M.	429
Thomson, R. F.	1056
Treco, R. M.	872

V

VanVlack, L. H.	741
VerSnyder, F. L.	397
Vicars, E. C.	275
Vreeland, T., Jr.	620

W

Walker, H. L.	200
Wells, Cyril	1080
Westbrook, J. H.	221
Wood, D. S.	620

SUBJECT INDEX

Activation energy

- alpha brass208-211, 215-217
- grain growth215-217
- recrystallization208-211
- aluminum277-283
 - grain boundary relaxation277-283
 - effect of magnesium additions on282-283
- steel593-597
 - first stage of tempering593-594
 - second stage of tempering595-597
 - variation with carbon content596-597

Aluminum

- effect on properties of molybdenum alloys286-313
- effect on recrystallization of molybdenum alloys314-332
- grain boundary migration in560-561, 564
- grain boundary relaxation 275-285
 - activation energy277-283
 - effect of magnesium additions on282-283
 - equation 277
- as a function of the parameter ($D_0 e^{Q/RT}$)..279-280
- correlation of frequency, energy of activation and temperature for277-278
- correlation of grain size, frequency, energy of activation and temperature278-279
- effect of alloying elements on275-285
 - width of relaxation band 284
- effect of frequency of vibration on 276
- effect of temperature .. 276
- hardness 227
 - log hardness vs. temperature 227

Aluminum (cont.)

- rigidity relaxation as a function of the parameter ($AD^{1.80} e^{Q/RT}$)280-281, 283

Aluminum alloy, trade designations

14S-T6

- stress-strain relations with biaxial tensile stresses. See Biaxial tensile stresses.

Aluminum-copper alloys

- deformation strength263-270
 - relation to mean free path between $CuAl_2$ particles263-270
 - equation 270
- deformation stress265-270
 - effect of planar mean free path on265-266, 268
 - effect of volume mean free path on265-270
- $CuAl_2$ particle dispersion
 - calculation of mean free path257-262
 - equations257-262
- rigidity relaxation as a function of the parameter ($AD^{1.80} e^{Q/RT}$)280-281
- stress-strain curves263-266
 - effect of mean free path of $CuAl_2$ particles on..263-266
 - effect of testing temperature263-266
- tensile properties
 - effect of dispersions on.249-270
 - method of determining 254-262

Aluminum-germanium alloys

- rigidity relaxation as a function of the parameter ($AD^{1.80} e^{Q/RT}$)280-281

Aluminum killed steel

- strain aging characteristics 344-361

- Aluminum-magnesium alloys**
 grain boundary relaxation 281-282
 correlation of grain size,
 frequency, energy of
 activation and temper-
 ature for281-282
 rigidity relaxation
 as a function of the
 parameter ($AD^{1.80} \nu e^{Q/RT}$) 283
- Aluminum-silver alloys**
 rigidity relaxation
 as a function of the
 parameter ($AD^{1.80} \nu e^{Q/RT}$)
280-281
- Aluminum-tin alloy**
 grains
 frequency of occurrence
 of various polygonal
 faces on 539
- Aluminum-zinc alloys**
 rigidity relaxation
 as a function of the
 parameter ($AD^{1.80} \nu e^{Q/RT}$) 280
- Anelasticity**
 boundary between anelastic
 and plastic behavior827-837
 definition and characteristics
 of787-789
 influence of stress and time
 on creep recovery787-812
 effect of stress decre-
 ment807-811
 relations between creep
 and creep recovery ...800-807
 strain-time relations for
 creep recovery789-800
 influence on tension, creep
 and relaxation812-827
 applications 826
 combination of anelastic
 and plastic behaviors .817-822
 during partial unloading 813-815
 modulus effects815-817
 relaxation phenomena ..822-826
- Annealing**
 of molybdenum and its alloys
 recrystallization effect
320-323, 325-332
- Annual Address of the President** 6
- Annual Dinner of ASM** 27
- Annual Meeting of ASM** .. 5
- Annual Report of the Secretary** 15
- Annual Report of the Treasurer** 10
- Armco iron**
 residual stress
 X-ray measurement of .672-673
 skewness index as a
 function of the rotation
 angle ψ 672-673
- Arsenic-indium system**
 See Indium-arsenic system.
- Austenite**
 in Cr-Ni-Mo-Ti (18-8-3-1) alloy
 electrolytic separation
444-445, 447-449
 properties449-460
- Austenite to martensite
 transformation**
 stainless steels 77-95
 effect of carbide precipitation
 on the beginning of
 transformation ..82-87, 93-94
 effect of composition on
 temperature of 77-95
 procedure for determining 80-85
- Austenite stabilizers**
 stainless steels
 chromium or nickel
 equivalents 78-80
- Austenitizing temperature**
 of high speed steel 18-4-1
 effect on grain size 481
 effect on impact strength
486-491
 relationship to hardness 477-484
- Austenitizing time**
 for high speed steel 18-4-1
 effect on grain size 481
 relationship to hardness 477-484
- Bend test**
 for evaluating molybdenum
 alloys 289
 results295-299

Beryllium

- determination of elastic constants850-852, 855-857
- effect on properties of molybdenum alloys286-313
- effect on recrystallization of molybdenum alloys ..314-332

Biaxial tensile stresses

- applied to Alcoa 14S-T6
 - constant stress ratio tests
 - ductility calculations695, 697, 700, 704-705
 - flow theory substantiation693-694, 696-697
 - fracture stresses vs. maximum stress
 - theory694, 696, 704
 - proportional limit vs. maximum stress
 - theory691-692
 - stress-strain relations 689-691
 - true stress-strain relations692-697
 - yield strength vs. distortion
 - energy theory 692
- test procedure687-689
- variable stress ratio tests
 - flow theory substantiation698-699, 701-705
 - slip theory inconsistencies 705
 - stress-strain relations695, 697-699, 701

Boron

- effect on properties of molybdenum alloys286-313
- effect on recrystallization of molybdenum alloys ..314-332

Brass

- beta phase fractions as a function of composition 556
- determination of elastic constants847-848, 850-852
- grains
 - frequencies of occurrence of various polygonal faces on 539
 - isolated by fracture .. 539

Brass, alpha

- grain growth211-218
 - effect of annealing
 - temperature212-214
 - effect of annealing time 211-214
 - effect of cold work211-214
 - effect of initial grain
 - size212-214
 - heat of activation215-217
 - effect of initial grain
 - size215-216
 - effect of prior deformation215-216
- recrystallization200-211
 - activation energy208-211
 - schematic representation 209
 - heat of activation208-211
 - effect of initial grain
 - size210-211
 - effect of prior deformation208-211
 - relation between recrystallized grain size and deformation206-207
 - relation between recrystallized grain size and initial grain size207-208
 - relation between recrystallized grain size and temperature of annealing206-207
 - times and temperatures for204-205, 210

Cadmium

- hardness 229
- log hardness vs temperature 229

Carbon

- effect on case hardenability781-782
- effect on properties of molybdenum alloys286-313
- effect on recrystallization of molybdenum alloys ..314-332
- in high speed steel 18-4-1
 - effect of amount on hardness477-483
 - effect of amount on impact strength486-491

Carburization

- contact catalysis theory
.....134, 146-147
- oxidizing potential theory
.....134, 143-144, 146-147
- stainless steels134-148
- apparatus 135
- procedure135-137
- with graphite138-148
 - air atmosphere ..138-141, 143
 - ammonia atmosphere 138-145
 - argon atmosphere 138-141, 143
 - correlation between depth
of carburization and
corrosion rates
.....139, 143, 146, 148
 - prior oxidized surface
.....138, 141-142, 144
 - Type 304138, 142, 146
 - Type 316138-146
 - Type 347138, 141, 146

Carburized steels

- hardenability1056-1079
 - AISI 33101067, 1071
 - AISI 4620 1068
 - AISI 48151068, 1071
 - AISI 50B20 1067
 - AISI 8117 .1066, 1068-1069, 1071
 - effect of boron on
.....1066, 1069, 1071
 - AISI 8620 1066
- case hardenability at various
carbon levels1064-1071
- core hardenability ...1064, 1069
- end-quench test for deter-
mining1056-1079
- trapezoidal end-quench
bar ...1057-1062, 1076-1077
- comparison of cooling
with standard bar
.....1059-1060, 1077
- comparison of harden-
ability with standard
bar1060, 1076-1077
- experimental problems
.....1060-1061
- method of obtaining
data from1061-1062

Carburizing steels, alloy

- effect of boron on case hard-
enability
alloys tested772-773
- as function of carbon
content781-782
- as function of quench
temperature781-782
- hardenability curves for
uncarburized steels ..772-773
- multiplying factor for boron 781
- of 4720 steel780-781
- of 8020 steel774-776
- of 9420 steel776-780
- effect of vanadium ...778, 783

Case hardenability

- of alloy carburizing steels
- effect of boron on. See
Carburizing steels, alloy.

Cells

- in human fat tissue 540

Chromium

- effect on properties of
molybdenum alloys286-313
- effect on recrystallization
of molybdenum alloys ..314-332

Chromium-nickel-molybdenum-titanium steel

- austenite and sigma separated
electrolytically from
18-8-3-1444-449
- characteristics of phases 458-460
- chemical analysis450-451
- electrode potential measure-
ments446-447, 451-458
- electronmicrographs
.....450, 455-456
- magnetic examination
.....445-446, 449-450
- photomicrographs. 450, 452-454

Cobalt

- effect on properties of
molybdenum alloys286-313
- effect on recrystallization
of molybdenum alloys ..314-332

Coefficients of expansion

titanium alloys1001-1003

Columbiumelastic constants determined
.....850-852**Confidential Technical Meeting on
Refractory Type Materials for
High Temperature Applications
—Cleveland, November 24 and
25, 1952 39****Constituents**

in high temperature alloys 397-428

Constitution diagrams

See Phase diagrams.

Copperhardness229-230, 233-235
log hardness vs temperature
.....229-230, 233-235
correlation with tensile
strength229, 233
single and polycrystals
.....229-230, 235

oxygen content

isotopic determination. See
under Isotopic analysis.**Copper-gold alloys**dependence upon temperature
of the rate of isothermal
transformation1037-1038
resistance-temperature
curves1031-1033**Copper-silver alloy**discontinuous precipitation in
.....566-568**Copper-zinc alloys**resistance-temperature
curves1031-1033**Creep**chromium-nickel steels ... 42-76
role of anelasticity in. See
Anelasticity.
total43, 45-46
equation 45**Creep recovery**role of anelasticity in. See
Anelasticity.**Creep-rupture curves**stainless steels ...114-115, 122-123
effect of carbon ...114-115, 122
effect of nitrogen ..114-115, 123**Creep-rupture properties**monel151-169, 181-195
effect of atmosphere on 181
stress vs minimum creep
rate189-195
effect of grain size on 189-195
effect of testing temper-
ature189-195
stress vs rupture life ...182-190
effect of grain size on 182-190
effect of testing temper-
ature182-190
stainless steels105-132
ductility116-117, 119
effect of carbon117, 119
effect of nitrogen117, 119
effect of testing temper-
ature117, 119
effect of carbon105, 108-110
effect of carbon and
nitrogen 111
effect of microstructure
on129-131
effect of nitrogen on
.....105, 111, 113, 115
effect of testing temperature
.....109-112, 114-127, 130-132
minimum creep rates
.....114, 120-121, 127, 130
variation as a function of
carbon plus nitrogen
content
.....114, 120-121, 127, 130
procedure for determining
.....106-108
rupture life 111-114, 118-119, 127
variation as a function
of carbon plus nitrogen
content
.....111-114, 118-119, 127
stress vs. minimum creep
rate111-112, 116

Creep-rupture properties (cont.)

- stainless steels
 - stress vs. rupture life ..
 -109-110, 115
 - stresses for specified rupture
 - times115-117
 - effect of carbon plus
 - nitrogen content ...115-117
 - effect of testing temper-
 - ature115-117

Creep-rupture tests

- monel158-159, 163-164
 - comparison of static recrystallization, equicohesion
 - and hardness163-164
 - oxide penetration during 158-159

Creep strength

- stainless steels 53-56
 - effect of carbon on 54-55
 - effect of columbium on . 55
 - effect of nitrogen on ... 54
 - variation with temperature
 - 53-56
 - Type 303 54
 - Type 304 53-54
 - Type 304L 53-54
 - Type 316 53, 55
 - Type 316L 53, 55
 - Type 321 53-54, 56
 - Type 347 53, 56

Deformation strength

- aluminum-copper alloys ..263-270
 - relation to mean free path
 - between CuAl_2 particles
 -263-270
 - equation 270

Deformation stress

- aluminum-copper alloys ..265-270
 - effect of planar mean free
 - path on265-266, 268
 - effect of volume mean free
 - path on265-270
 - correlation with strain hard-
 - ening index252-253

Delayed yield phenomenon..620-637

- measurement of plastic and
 - anelastic microstrain .626-628
 - typical record of 626
- mechanism of620-637
- procedure for determining .623-628
- rapid-load tension tests ..624-628
 - delay time vs. stress 624, 627-628
- repeated stress-pulse tests 624-626
 - activation energy for the
 - recovery process 628
 - cumulative time at stress
 - to yield vs. aging time
 -625-626, 628
 - typical record of 625
 - static tension tests 623
 - static stress vs. strain .. 623

Dilatometric measurements

- of steels containing silicon
 - effect of silicon during
 - tempering509-513

Distortion energy theory

- applied to biaxially stressed
 - 14S-T6
 - agreement with yield
 - strength values 692

Ductility

- of biaxially stressed 14S-T6
 -695, 697, 700, 704-705
- monel183-186, 191-197
 - effect of composition ... 193
 - influence of grain size
 -183-186, 191-192, 194, 197
 - influence of stress
 -183-186, 191-192, 194-197
 - influence of testing tempera-
 - ture 183-186, 191-192, 194-197

Elastic constants

- determined by ultrasonics.
 - See under Ultrasonics.

Election of Officers 26**Electrical resistivity measurements**

- of steels containing silicon
 - effect of silicon during
 - tempering513-514

- Electrode potential measurements**
 of austenite and sigma
 separated from Cr-Ni-Mo-Ti
 (18-8-3-1) alloy
446-447, 451-458
- Electrolytic separation**
 of austenite and sigma
 from Cr-Ni-Mo-Ti (18-8-3-1)
 alloy444-445, 447-449
- Electron micrographs**
 of austenite and sigma
 separated from Cr-Ni-Mo-Ti
 (18-8-3-1) alloy ..450, 455-456
 iron-carbon alloy 602
 showing interface between
 pearlite and tempered
 martensite570-571
- Elevated temperature hardness**
 of binary molybdenum
 alloys299-301
 of 8 Cr-1 Mo steel390-391
 relationship to strength 391-393
 of 18 Cr-8 Ni stainless
 steels387, 389-390
 relationship to strength
 and creep391-393
 hot hardness tester378-383
 influence of duration of
 loading on386-389
 influence of specimen prep-
 aration on384-386
 of plain carbon steels378-383
 relationship to strength
 and creep391-393
- Elevated temperature impact
 properties**
 of nodular iron368, 370-371
- Elevated temperature properties**
 monel
 influence of grain size
 on177-197
 of nodular iron365-370
 of zirconium-oxygen alloys
885-889
- Embrittlement**
 of Fe-Ni-Cr alloys
 by sigma phase437-440
- Embrittlement (cont.)**
 of SAE 3140 steel
 effect of hardness on impact
 energy curves. See Impact
 energy curves.
 effect of heat treatment on.
 See under Temper brittleness.
- Endurance limit**
 of temper-brittle steel SAE 5140.
 See Temper-brittle steel.
- Epsilon carbide**
 calculation of chemical
 composition597-598
- Equilibrium diagrams**
 See Phase diagrams.
- Euler's law 534**
- Fabricability**
 of binary molybdenum
 alloys290-292
- Fatigue properties**
 titanium alloys998-1001, 1003
 at low temperatures
998-1001, 1003
 effect of notch on ...998-1000
 typical fractures ...1001, 1003
- Flow stress**
 in steels
 effect of mean distance
 between particles on..250-251
- Flow theory**
 applicability to biaxially stressed
 14S-T6693-699, 701-705
- Forgings**
 tensile properties1096-1099
 longitudinal1098-1099
 effect of cooling rate
1098-1099
 transverse1097-1098
 effect of cooling rate
1097-1098
- Forging steel**
 microstructure 1088
 air-cooled SAE 1045
 specimen 1088
 furnace-cooled SAE 1045
 specimen 1088

Forging steel (cont.)

- tensile properties
 -1086-1096, 1099-1113
- correlation coefficients
 -1086-1087, 1092, 1103
- effect of angle of test on
 - ..1099-1101, 1108, 1110-1111
- elongation vs. angle of
 - test 1108
- reduction of area vs.
 - angle of test 1108
- effect of homogenization
 - treatment on
 -1088-1089, 1094-1096
- quenched and tempered
 - specimens1101-1111
- effect of angle of test
 - on1108, 1110-1111
- effect of reduction by
 - forging 1101
- reduction of area vs. reduction
 - by forging 1088-1089,
 - 1092-1096, 1103-1107, 1110
- effect of homogenization
 - treatment on
 -1088-1089, 1094-1096
- effect of tempering
 - temperature 1103, 1105-1106
- regression lines
 - 1086-1087, 1092, 1103-
 - 1104, 1106-1107, 1109-1110
- tensile strength vs.
 - longitudinal reduction
 - of area1103-1104, 1107
- yield strength vs.
 - longitudinal reduction
 - of area1103-1104, 1106
- yield strength vs.
 - transverse reduction
 - of area1103-1104, 1107
- specimens containing ferrite
 - and pearlite
 -1088-1096, 1099-1101
- specimens quenched and
 - tempered1101-1113
- transverse mechanical prop-
 - erties in1080-1121
- materials and specimen
 - preparation1081-1085

Forging steel (cont.)

- transverse reduction of area
 - frequency curves ..1085-1086
- furnace-cooled specimens 1085
- quenched and tempered
 - specimens 1086

Fracture, mode of

- stainless steels
 - effect of creep or rupture
 - test exposure on 70, 73

Fracture strength

- of biaxially stressed 14S-T6
 - agreement with maximum
 - stress theory694, 696, 704

Free machining steel

- AISI B-1112 and B-1113 alloys
- machinability742, 747
 - effect of inclusion com-
 - position on750-752
 - effect of inclusion size
 - and shape on742-746
 - effect of mechanical
 - working on 749
 - effect of number of
 - inclusions on 748
 - effect of silicon on ...
 -744, 746-748
 - effect of sulphur content
 - on749-750

Furnace

- for melting zirconium and
 - other refractory metals.862-871

Grain boundary energy

- variation with orientation
 - between crystals545-548
- variation with thickness at
 - various temperatures below
 - melting point554-555

Grain boundary melting551-555

- replacement of grain corners
 - by liquid at temperatures
 - below the melting point
 -552-555
 - equations552-553

Grain boundary melting (cont.)

- volume free energy required
 - to produce liquid553-555
- as a function of temperature553-555
- as a function of thickness
 -553-555

Grain boundary migration

- in strained aluminum.560-561, 564

Grain boundary relaxation

- aluminum275-285
 - activation energy277-283
 - effect of magnesium
 - addition on282-283
 - equation 277
 - as a function of the
 - parameter ($D_{\text{re}}^{Q/RT}$) ..279-280
 - correlation of frequency,
 - energy of activation and
 - temperature for277-278
 - correlation of grain size,
 - frequency, energy of
 - activation and temperature278-279
 - effect of alloying elements
 - on275-285
 - width of relaxation band 284
 - effect of frequency of
 - vibration on 276
 - effect of temperature .. 276
- aluminum-magnesium alloys
 - correlation of grain size,
 - frequency, energy of
 - activation and temperature for281-282
- iron
 - as a function of the
 - parameter ($D_{\text{re}}^{Q/RT}$) ..279-280

Grain growth

- alpha brass211-218
 - effect of annealing temperature212-214
 - effect of annealing time.211-214
 - effect of cold work211-214
 - effect of initial grain
 - size212-214
 - heat of activation215-217

Grain growth (cont.)

- alpha brass
 - heat of activation
 - effect of initial grain
 - size215-216
 - effect of prior deformation215-216

Grain orientation

- of low carbon steel strip
 - effect of rolling temperature
 - on333-343

Grains

- frequency of occurrence of
 - various polygonal faces
 - on 539
- aluminum-tin alloy 539
- brass 539
- comparison with soap froth 539
- comparison with vegetable
 - cells 539
- isolated by fracture..... 539

Graphite

- oxygen content
 - isotopic determination..762, 766

Hafnium

- furnace for melting862-871

Hardenability

- of alloy carburizing steels.772-773
- carburized steels1056-1079
 - AISI 33101067, 1071
 - AISI 4620 1068
 - AISI 48151068, 1071
 - AISI 50B20 1067
 - AISI 81171066, 1068
 - effect of boron on
 -1066, 1069, 1071
 - AISI 8620 1066
- case hardenability at various
 - carbon levels1064-1071
- core hardenability ...1064, 1069
- end-quench test for determining1056-1079
- trapezoidal end-quench
 - bar1057-1060
- comparison of cooling with
 - standard bar1059-1060

Hardenability (cont.)

- carburized steels
 - trapezoidal end-quench bar
 - experimental problems
 -1060-1061
 - method of obtaining data
 - from1061-1062

Hardness

- of high speed steel 18-4-1
 - effect of carbon content
 - on477-483
 - effect on impact strength
 -488, 490
 - relationship to austenitizing
 - temperature and time.477-484
 - relationship to tempering
 - temperature and time.483-490
- pure metals222-241
 - as a function of the homol-
ogous temperature ...222-223
 - as a function of melting
point222-223
 - correlation between constant
A and the absolute melting
point 233, 235-236
 - correlation between constant
A ($H = Ae^{-BT}$) and heat
content of liquid metal at
melting point 232-233, 235-236
 - correlation between constant
B ($H = Ae^{-BT}$) and the
reciprocal melting point
.....237-240
 - functional relations224-231
 - fundamental correlations
.....231-239
 - hardness-temperature data 234
 - log hardness vs. temperature
.....227-231
 - aluminum 227
 - cadmium 229
 - copper229, 233
 - molybdenum227, 231
 - thallium228, 232
 - tin 230
 - zinc 228
 - qualitative observations 222-223
 - temperature dependence
.....221-241

Hardness (cont.)

- pure metals
 - temperature dependence
 - equation 231, 236-238, 240-241
 - functions proposed for
.....224-225
 - of steels containing silicon
 - effect of silicon on501-507
 - of temper-brittle steel
 - effect on impact energy curve.
See Impact energy curves.
- titanium
 - effect of impurities on..235-236
- titanium alloys
 - at low temperatures..1000-1001
- titanium-oxygen alloys 1023-1024

Hardness tester

- for elevated temperature
testing378-383

Heat of activation

- See Activation energy.

High speed steel

- W-Cr-V (18-4-1)
 - effect of austenitizing
 - temperature and time
 - on grain size 481
 - on hardness477-484
 - on impact properties..486-491
 - effect of carbon content
 - on hardness477-483
 - on impact strength ..486-491
 - effect of tempering time
 - and temperature
 - on hardness483-490
 - on impact strength ..486-491
 - effect of vanadium content
 - on hardness480-481, 484
 - impact strength486-491
 - microstructure481-483

High temperature alloys

- alloy M252 (Ni base)
 - microconstituents in ...397-428
- alloy 16-25-6 (Fe base)
 - microconstituents in ...397-428
- alloy 1336 (Co base)
 - microconstituents in ...397-428

High temperature alloys (cont.)

- alloy 1336 (Nb + Ta)
 - microconstituents in ...397-428
- Turballoy 13397-428

Hot hardness tester

- results with various steels.377-396

Impact energy curves

- for SAE 3140 steel733-734
- effect of hardness on ...734-735

Impact properties

- of Fe-Ni-Cr alloys
 - effect of sigma phase on.437-440
- of high speed steel (18-4-1)
 -486-491
- of nodular iron at elevated
 - temperatures368, 370-371
- of SAE 3140 steel
 - effect of hardness on. See
 - Impact energy curves.
 - effect of heat treatments
 - on725-731
- of steels containing silicon
 - effect of silicon on521-523
- of temper-brittle steel710-724

Impact strength

- titanium alloys
 - at low temperatures
 -1000-1001, 1003-1004
 - typical fractures ...1003-1004

Inclusions

- effect on machinability
 - of AISI B-1112 and B-1113
 - alloys. See under Free
 - machining steel.

Indium

- effect on properties of
 - molybdenum alloys286-313

Indium-arsenic system

- metallographic analysis ..
-678, 681-684
- phase diagram679-680
- thermal analysis678-679
- X-ray analysis679-680

Interface motions

- during transformation ...561-563

Iron

- effect on properties of
 - molybdenum alloys286-313
- effect on recrystallization of
 - molybdenum alloys314-332
- grain boundary relaxation
 - as a function of the
 - parameter ($Dre^{Q/RT}$) .279-280
- oxygen content
 - isotopic determination. See
 - under Isotopic analysis.

Iron-carbon alloys

- single crystals579-582
 - method of producing ... 579
- oscillation diffraction
 - patterns581-582
- rotation diffraction
 - patterns 580

Iron-nickel-chromium alloys

- sigma formation in433-437
- effect on impact properties
 -437-440

Isotopic analysis

- of oxygen in metals and metal
 - oxides
 - apparatus760-761
- copper and iron-oxygen
 - samples analyzed763-765
- determination of oxygen
 - in graphite762-766
- other methods of analysis
 -758-759
 - advantages of isotopic
 - method 766
- preparation of O^{18} master
 - alloys 762
- principles of method ...759-760
- procedure761-762

Lattice parameters

- of microconstituents in high
 - temperature alloys400-411

Low carbon steel

- texture of rolled strip
 - effect of rolling temperature
 - on333-343

Lüders bands

- in titanium tensile specimens
.....988-990

Machinability

- of AISI B-1112 and B-1113 alloys
 - correlation with inclusion characteristics. See under Free machining steel.
- stainless steel, Type 304
 - effect of saw wear on cutting time 948
 - comparison with titanium 948
- titanium957-965
 - effect of arsenic on.957, 961-962
 - effect of beryllium on ..
.....957, 959, 963
 - effect of boron on
.....957-958, 961-962
 - effect of carbon on
.....957-958, 962-963
 - effect of germanium on
.....957, 961, 963
 - effect of phosphorus on
.....957, 961-962
 - effect of selenium on ...
.....957, 960, 962
 - effect of silicon on
.....957, 959, 962-963
 - effect of sulphur on
.....957, 959-960, 962-963
 - effect of tellurium on ...
.....957, 960-962
- high purity iodide vs. magnesium-reduced titanium957-960
- saw rating vs. turning index for various titanium alloys962-964
- correlation with Vickers hardness and ultimate strength963-964
- titanium alloys941-971
 - effect of saw wear on cutting time 948
 - comparison with Type 304 stainless steel 948
 - effect of test variables ..955-956
 - feed vs. load955-956

Machinability (cont.)

- titanium alloys
 - influence of insoluble phases941-971
 - lathe test944-947, 954-962
 - method of evaluating.946-947
 - profilometer measure-ments 954
 - testing equipment ...944-946
 - saw test
....947-949, 957-964, 968-969

Magnetic analysis

- of austenite and sigma separated from Cr-Ni-Mo-Ti (18-8-3-1) alloy
.....445-446, 449-450

Magnetic permeability

- stainless steels
 - effect of creep or rupture test exposure on 73-75

Manganese

- effect on properties of molybdenum alloys286-313
- effect on recrystallization of molybdenum alloys314-332

Martensite

- tempering of
 - effect of silicon on498-532

Martensite transformation temperature

- in titanium binary alloys..934-939
- concentration vs. transformation temperature 935-939
- titanium-chromium ..936-939
- titanium-columbium
.....936, 938-939
- titanium-iron935-939
- titanium-manganese .936-938
- titanium-molybdenum
.....935-936, 938-939
- titanium-tantalum ...
.....936, 938-939
- titanium-tungsten ...936, 938
- titanium-vanadium ..
.....935-936, 938-939

Maximum stress theory

- applied to biaxially stressed
14S-T6
agreement with fracture
stresses694, 696, 704
- agreement with proportional
limit691-692

Mechanical properties

- of binary molybdenum alloys
.....293-299
- of recrystallized molybdenum
.....321-323
- of recrystallized molybdenum
alloys325-332
- stainless steels
 - effect of creep test exposure
on 58-60
- titanium949-953, 972-992
 - dependence of elastic modulus
on temperature 981
 - dependence of elongation
on temperature979-981
 - effect of strain rate on
.....979-981
 - dependence of fracture stress
on temperature978-980
 - effect of strain rate on
.....978, 980
 - dependence of reduction
of area on temperature
.....980-981
 - effect of strain rate on
.....980-981
 - dependence of yield strength
on temperature977-979
 - effect of strain rate on
.....977, 979
 - dependence of ultimate strength
on temperature 978
 - effect of strain rate on 978
 - effect of arsenic on 950
 - effect of beryllium on .. 949
 - effect of boron on 949
 - effect of carbon on 949
 - effect of germanium on . 950
 - effect of phosphorus on. 950
 - effect of selenium on ... 950
 - effect of silicon on950-953
 - effect of sulphur on949-950

Mechanical properties (cont.)

- titanium
 - effect of tellurium on .. 950
 - fracture appearance at
different temperatures
of testing985, 987-988
 - plastic portion of true stress-
strain curve981-983
 - strain aging effects972-992
 - yield point phenomenon 983-984
- titanium alloys993-1007
 - at low temperatures ..993-1007
 - effect on notch sensitivity
.....996-997
 - effect of testing temper-
ature995-997
- of zirconium-oxygen alloys. See
Zirconium-oxygen alloys.

Mechanical properties, transverse

- forging steel, SAE 1045 .1080-1121
- materials and specimen
preparation1081-1085

Mechanical working

- effect on machinability
of free machining steel . 749

Medium alloy steel

- effect of silicon on tempering
.....498-532

Melting temperatures

- titanium-oxygen alloys .1019-1020

Metal oxides

- isotopic determination of oxygen
content. See Isotopic analysis.

Microconstituents

- in high temperature alloys
.....397-428

Microstructure

- of binary molybdenum alloys
.....300-306
- classification557-561
- types of interfaces between
crystals558-561
- coherent and incoherent
boundaries558-561

Microstructure (cont.)

- of Cr-Ni-Mo-Ti (18-8-3-1)
 - alloy450, 452-454
- distribution of dihedral angles
 - resulting from random sectioning543-545
- distribution of minor liquid phase in polycrystalline matrix547, 549
- of Fe-Ni-Cr alloys
 - sigma phase432-433
- forging steel, SAE 1045 .1087-1088
 - air-cooled specimen 1088
 - furnace-cooled specimen 1088
- grain boundary energy
 - variation with thickness at various temperatures below melting point554-555
- grain boundary melting ..551-555
- replacement of grain corners
 - by liquid temperatures below the melting point552-555
 - equations552-553
- volume free energy required to produce liquid
 - as a function of temperature553-555
 - as a function of thickness553-555
- of high speed steel (18-4-1)481-483
- of high temperature alloys 397-428
- of indium-arsenic alloys ..681-684
- interface motions during trans-formation561-563
- formation of a nucleus by coherent fluctuations in the vicinity of disordered grain boundary562-563
- interfaces and precipitation562-571
- discontinuous precipitation564-571
- measurement of555-557
- brass
 - beta phase fractions as a function of composition 556

Microstructure (cont.)

- measurement of
 - grid for grain boundary area measurement by intercept counting 557
- plane and curved grain boundaries536-545
- grain shape and grain growth536-545
- disappearance of bubbles
 - by diffusion537-538
- polyphase alloys541-545
 - variation of dihedral angle with ratio of interface energies541-542
- of recrystallized molybdenum319-321
- of recrystallized molybdenum alloys322-324, 326
- requirements of space-filling534-545
- basic topological relations534-541
- equations ...534-535, 537-538
- stainless steels 60-73
 - changes during creep or rupture test exposure. 60-73
 - Type 303 61-66
 - Type 30461, 71-73
 - Type 304L60-61, 63-64
 - Type 316CB61-62, 67-68
 - Type 316L61-62, 65-66
 - Type 32161, 64-69, 71-73
 - Type 34761, 71-73
- of steels containing silicon507-509
- structures with anisotropic interfaces545-548
- titanium alloys951-953
 - titanium - 0.07% arsenic 951, 953
 - titanium - 0.02% beryllium952-953
 - titanium - 0.57% boron .951, 953
 - titanium - 0.47% carbon 951, 953
 - titanium - 0.25% germanium952-953
 - titanium - 0.39% phosphorus952-953
 - titanium - 0.99% selenium952-953

Microstructure (cont.)

titanium alloys

titanium - 0.25% silver .951, 953

titanium - 0.32% sulphur

as Ti_3S_4 951, 953

titanium - 0.118% sulphur

as MoS_2 951, 953

titanium - 0.47% tellurium

.....952-953

titanium, unalloyed952-953

titanium-oxygen alloys .1012-1019

of two-phase alloy543-544

showing different types

of grain junction 544

of zirconium-nickel alloys.897-898

of zirconium-oxygen alloys

.....883-884

of zirconium-silicon alloys 906-912

of zirconium-tin alloys ...921-927

Minimum creep rate intercept

variations with stress 55-57

effect of temperature .. 57

Type 304 stainless steel 57

Type 304L stainless steel 57

Type 316CB stainless steel 57

Type 316L stainless steel 57

Type 321 stainless steel 57

Type 347 stainless steel 57

Modulus of elasticity

determined ultrasonically for

brass847-848, 850-852

beryllium850-852

columbium850-852

thorium850-852

titanium850-852

Type 347 stainless steel.848-852

uranium850-852

vanadium850-852

zirconium850-852

influence of anelasticity on

.....815-817

Molybdenum

elastic constants determined

.....855-857

furnace for melting862-871

hardness227, 231

log hardness vs. reciprocal

temperature227, 231

Molybdenum (cont.)

hardness

log hardness vs. temperature

.....227, 231

recrystallization of. See under

Recrystallization.

Molybdenum alloys, binary

alloys investigated289-291

effect of deoxidation312-313

elevated temperature hard-

ness299-301

fabricability290-292

microstructure300-306

most effective alloying

additions305-311

preparation of alloys287-288

recrystallization of. See under

Recrystallization.

room temperature properties

.....293-299

strength-elongation

correlation305-309

strength-hardness

correlation307-309

sintering characteristics ..291-292

test methods287-289

Monel

creep-rupture properties .

.....151-169, 181-195

effect of atmosphere on.. 181

stress vs. minimum creep

rate189-195

effect of grain size on .189-195

effect of testing tem-

perature189-195

stress vs. rupture life ..182-190

effect of grain size on.182-190

effect of testing tem-

perature182-190

creep-rupture tests

.....158-159, 163-164

comparison of static recryst-

tallization, equicohesion

and hardness163-164

oxide penetration during

.....158-159

ductility183-186, 191-197

effect of composition 193

Monel (cont.)

- ductility
 - influence of grain size..
 -183-186, 191-192, 194-197
 - influence of stress
 -183-186, 191-192, 194-197
 - influence of testing temperature
 -183-186, 191-192, 194-197
- high temperature properties177-197
 - influence of grain size on177-197
- recrystallization .158-163, 171-176
 - cold work vs. temperature for159, 161
 - during creep-rupture testing160-163
 - hardness vs. temperature158, 161
- stress-rupture properties152-159, 164-170
 - graphical method of extrapolating and interpolating short-time data ..167-169
 - stress vs. minimum creep rate effect of cold work ..166-167
 - effect of testing temperature166-167
 - stress vs. rupture life..
 - ...152-159, 164-165, 167-170
 - effect of cold work ..
 -153-159, 164-165, 167
 - effect of testing temperature ..153-154, 156-157, 164-165, 167-170

Nickel

- effect on properties of molybdenum alloys286-313
- effect on recrystallization of molybdenum alloys..314-332

Nickel-iron alloys

- order-disorder transformation1051-1054
- dilatometric measurements1052-1053
- phase fields for ordering reaction 1053

Niobium

- furnace for melting.....862-871

Nodular iron

- elevated temperature impact properties ...368, 370-371
- elevated temperature tensile properties .365-367, 369-370
- microstructure
 - annealed364-365
 - as-cast363-364
- stress-rupture data at 1200 °F368-369, 371-373
- fracture structure371-373

Notch sensitivity factor

- of temper-brittle steel ... 718

Order-disorder transformation

- as a classical phase
 - change1029-1055
- arguments against and rebuttal1039-1042
- analogy with established second-order transformations1041-1042
- electrical resistance.1039-1040
- hysteresis 1041
- microstructure 1041
- specific heat 1040
- X-ray diffraction ..1040-1041
- consequences of1042-1044
 - impact upon ordering theory 1044
 - nature of the ordered and disordered phases . 1042
- equilibrium coexistence of two phases in the ordering transformation interval1034-1036
- evidence in support of .1031-1039
- ordered and disordered phase coexistence1036-1037
- metallographic evidence1036-1037
- X-ray evidence 1036
- published evidence of a discontinuous ordering transformation 1034
- dilatometric observations.1034
- resistivity measurements.1034

Order-disorder trans. (cont.)

- as a classical phase change
- rate of the ordering trans-formation1037-1039
- dependence upon temper-ature 1038
- nickel-iron alloys1051-1054
- dilatometric measurements on1052-1053
- phase fields for ordering reaction 1053

Orowan's equation266-270

Oxygen

- effect on properties of zirconium. See Zirconium-oxygen alloys.
- in metals
- isotopic determination. See under Isotopic analysis.

Pearlite

- orientation relationships in568-571

Phase diagrams

- indium-arsenic679-680
- titanium-oxygen1012-1014
- zirconium-nickel, partial .. 895
- beta field 896
- zirconium-silicon903-905
- zirconium-tin918-919

Phosphorus

- effect on properties of molybdenum alloys286-313

Plastic deformation

- role of anelasticity in
- 817-822, 827-837

Poisson's ratio

- determined ultrasonically for
- brass847-848, 850-852
- beryllium850-852, 855-857
- columbium850-852
- molybdenum855-857
- thorium850-852
- titanium850-852, 855-857
- Type 347 stainless steel
- 848-852

Poisson's ratio (cont.)

- determined ultrasonically for
- uranium850-852
- vanadium850-852
- zirconium850-852, 855-857

Precipitation

- discontinuous564-566
- analogy with recrystalli-zation 564
- copper-silver alloy 566
- zinc-copper alloy564-565

President's Annual Address 6

Proportional limit

- of 14S-T6 stressed biaxially
- agreement with maximum
- stress theory691-692

Recrystallization

- alpha brass201-211
- activation energy208-211
- schematic representation 209
- heat of activation208-211
- effect of initial grain
- size210-211
- effect of prior defor-mation208-211
- relation between recrystal-lized grain size and de-formation206-207
- relation between recrystal-lized grain size and ini-tial grain size207-208
- relation between recrystal-lized grain size and tem-perature of annealing.206-207
- times and temperatures for
-204-205, 210
- analogy with discontinuous
- precipitation 564
- of molybdenum
- effect of annealing temper-ature on microstructure
- 320-321
- effect on tensile properties
-321-323
- grain sizes319-321
- recrystallization character-istics320-322

Recrystallization (cont.)

- of molybdenum alloys
 - alloys tested315-317
 - effect of annealing on...325-332
 - effect on tensile properties
 -325-332
 - relationship to alloy con-
 - centration327-329
 - grain refining action of al-
 - loying additions 326
 - microstructures ...322-324, 326
- monel158-163, 171-176
 - cold work vs. tempera-
 - ture for159, 161
 - during creep-rupture
 - testing160-163
 - hardness vs. temperature
 -158, 161

Relaxation

- role of anelasticity in. See
Anelasticity.

Relaxation rigidity

- as a function of the
 - parameter ($AD^{1.00} \nu e^{Q/RT}$)
 -280-281, 283
 - aluminum280-281, 283
 - aluminum-copper alloys .280-281
 - aluminum-germanium
 - alloys280-281
 - aluminum-magnesium
 - alloys 283
 - aluminum-silver alloys .280-281
 - aluminum-zinc alloys .. 280

Residual stresses

- Armco iron
 - X-ray measurement of .672-673
 - skewness index as a func-
 - tion of the rotation an-
 - gle ψ 672-673
- in manganese oil hardening
 - tool steel
 - effect of quenching and
 - tempering on605-615
 - optical interference method
 - for determining607-612
 - curvature measurements 609-611
 - graph showing curvature
 - variation with metal re-
 - moved 610

Residual stresses (cont.)

- optical interference method
 - metal layer removal tech-
 - niques607-609
 - stress calculation611-612
- in steel, FS 1050
 - X-ray measurement of .670-672
 - decrease in the biaxial stress
 - sum as a function of
 - the applied bending
 - stress670-672
 - intensity distribution about
 - the apparent maxi-
 - mum of the broadened
 - 211 K_α -doublet670-671
 - in steel, high carbon638-676
 - stress measurements of
 - martensitic phase .654-661
 - effect of cold work on .655-657
 - effect of electrolytic
 - polishing on657-659
 - effect of stressing be-
 - yond the yield strength
 - on658-660
 - X-ray measurement of .638-676
 - diffraction pattern obtained
 - using various radia-
 - tions645-646
 - effect of specimen orienta-
 - tion on line sym-
 - metry646-647
 - experimental necessities
 - for determining ...642-644
 - principles639-642
 - technique644-653
 - variation of "d" value with
 - orientation of speci-
 - mens652-653
 - variation in relative inten-
 - sity with 2θ 647-651
 - correction factors to com-
 - pensate for intensity
 - variation 647-651, 661-666
 - in tool steel607-617
 - curvatures induced in
 - specimens607-609
 - by etching607-609
 - by lapping608-609

Residual stresses (cont.)

in tool steel

- effect of etching on ...
..... 607-609, 614-615
- effect of grinding on
..... 609, 614-615
- effect of lapping on....
..... 608-609, 614-615
- effect of tempering on sur-
face stress 612-614, 617
- equations for determin-
ing 611

Resistivity

- of zirconium-oxygen alloys
..... 879-881

Retained austenite

- effect of silicon on transition
temperatures 504-505

Rimmed steel

- strain aging characteristics
..... 344-361

Rolling temperature

- effect on texture
of low carbon steel strip .333-343

Rupture

- chromium-nickel steels .. 42-76

Secretary's Annual Report . 15**Shear modulus.** See Modulus of elasticity.**Sigma phase**

- in Cr-Ni-Mo-Ti (18-8-3-1) alloy
electrolytic separation
..... 444-445, 447-449
- properties 449-460
- in Fe-Ni-Cr alloys of Types
310, 330 and Incoloy
effect on impact properties
and hardness 437-440
- effect of silicon on 434-435
- limiting composition free of
sigma 436-437
- sigma boundaries 433-436

Silicon

- effect on machinability
of free machining steel
..... 744, 746-748

Silicon (cont.)

- effect on properties of
molybdenum alloys ...286-313
- effect on recrystallization of
molybdenum alloys314-332
- effect on tempering of martensite
dilatometric measurements
..... 509-513
- electrical resistivity meas-
urements 513-514
- hardness effects 501-507
- relationship to tempering
time 505-507
- microstructures 507-509
- properties vs. tempering
time 521-523
- specific volume measure-
ments 514-516
- steels tested 499-500
- theory regarding 520-525
- X-ray diffraction meas-
urements 516-520
- in Fe-Ni-Cr alloys
effect on sigma formation
..... 434-435

Slip theory

- inconsistencies for biaxially
stressed 14S-T6 705

Soap bubbles

- disappearance of cells by
diffusion 537-538
- with increasing fraction of
liquid phase 549-550

Specific volume measurements

- of steels containing silicon
effect of silicon during
tempering 514-516

Stainless steels

- austenite to martensite trans-
formation 77-95
- effect of carbide precipita-
tion on the beginning of
transformation ..82-87, 93-94
- effect of composition on
temperature of 77-95
- procedure for determining .80-85

Stainless steels (cont.)

austenite stabilizers	
chromium or nickel equivalents	78-80
carburization	134-148
apparatus	135
with graphite	134-147
air atmosphere ..	138-141, 143
ammonia atmosphere ..	138-145
argon atmosphere ..	138-141, 143
correlation between depth of carburization and corrosion rates	139, 143, 146, 148
prior oxidized surface	138, 141-142, 144
Type 304	138, 142, 146
Type 316	138-146
Type 347	138, 141, 146
procedure	135-137
chromium-nickel	
creep and rupture	42-76
creep-rupture curves	
effect of carbon ...	114-115, 122
effect of nitrogen ..	114-115, 123
creep-rupture properties ..	105-132
ductility	116-117, 119
effect of carbon	117, 119
effect of nitrogen ...	117, 119
effect of testing temperature	117, 119
effect of carbon ...	105, 108-110
effect of carbon and nitrogen	111
effect of microstructure on	129-131
effect of nitrogen on ..	105, 111, 113, 115
effect of testing temperature ..	109-112, 114-127, 130-132
minimum creep rates ..	114, 120-121, 127, 130
variation as a function of carbon plus nitrogen content	114, 120-121, 127, 130
procedure for determining	106-108
rupture life ..	111-114, 118-119, 127

Stainless steels (cont.)

creep-rupture properties	
rupture life	
variation as a function of carbon plus nitrogen content ..	111-114, 118-119, 127
stress vs. minimum creep rate	111-112, 116
stress vs. rupture life ..	109-110, 115
stresses for specified rupture times	115-117
effect of carbon plus nitrogen content	115-117
effect of testing temperature	115-117
creep-rupture strength	
effect of molybdenum ..	48-50, 52
creep strength	53-56
effect of carbon on	54-55
effect of columbium on.	55
effect of nitrogen on. ..	54
variation with temperature	53-56
Type 303	54
Type 304	53-54
Type 304L	53-54
Type 316	53, 55
Type 316L	53, 55
Type 321	53-54, 56
Type 347	53, 56
delta factor vs. M_s temperature	96-97, 101
elongation at rupture vs. rupture time	46-55, 57-58
effect of temperature ..	46-55
Type 304	50
Type 304L	47
Type 316CB	49
Type 316L	48
Type 321	51
Type 347	52
hardness vs. hardening temperature	97-98
431 + Mo alloy	97-98
machinability	948
effect of saw wear on cutting time	948
comparison with titanium	948

Stainless steels (cont.)

- magnetic permeability ... 73-75
 - changes during creep or rupture test exposure ... 73-75
- mechanical properties
 - effect of creep test exposure on 58-60
- microstructure
 - changes during creep or rupture test exposure . 60-73
 - Type 303 61-66
 - Type 304 61, 71-73
 - Type 304L 60-61, 63-64
 - Type 316CB 61-62, 67-68
 - Type 316L 60-62, 65-66
 - Type 321 61, 64-69, 71-73
 - Type 347 61, 71-73
- minimum creep rate intercept 55-57
 - effect of temperature .. 57
 - Type 304 57
 - Type 304L 57
 - Type 316CB 57
 - Type 316L 57
 - Type 321 57
 - Type 347 57
- mode of fracture
 - effect of creep or rupture test exposure on 70, 73
- M_s temperature ... 88-93, 102-103
 - effect of annealing temperature on 102-103
 - effect of carbon plus nitrogen on 88
 - effect of chromium 88-90
 - effect of manganese ... 89, 91
 - effect of nickel 88-90
 - effect of quenching rate. 102-103
 - effect of silicon 89, 91-92
 - equation 92
 - measured vs. calculated values 92-93
- precipitated carbide
 - after exposure to elevated temperatures 126-128
- precipitated nitride
 - after exposure to elevated temperatures 126-128
- reduction of area at rupture vs. rupture time 46-55, 57-58

Stainless steels (cont.)

- reduction of area at rupture vs. rupture time
 - effect of temperature .. 46-55
 - Type 304 50
 - Type 304L 47
 - Type 316CB 49
 - Type 316L 48
 - Type 321 51
 - Type 347 52
- retained austenite 117-118, 120-127
 - after creep-rupture tests 120-121, 126-127
 - effect of carbon content 126-127
 - effect of cold work .. 126-127
 - effect of nitrogen content 126-127
 - effect of testing temperature 126
 - after exposure to elevated temperatures 117-118, 120, 122-127
 - effect of carbon content 124
 - effect of cold work 120, 125, 127
 - effect of nitrogen content 124
 - effect of testing temperature 124
- stress vs. minimum creep rate
 - effect of temperature .. 46-55
 - Type 303 53
 - Type 304 50
 - Type 304L 47, 53
 - Type 316CB 49
 - Type 316L 48
 - Type 321 51, 53
 - Type 347 52
- stress vs. ratio of elongation at rupture to time at rupture 46-55
 - effect of temperature .. 46-55
 - Type 304 50
 - Type 304L 47
 - Type 316CB 49
 - Type 316L 48
 - Type 321 51
 - Type 347 52

Stainless steels (cont.)

- stress vs. time for beginning of tertiary creep or time for rupture 46-56
- effect of temperature... 46-55
 - Type 304 50
 - Type 304L 47
 - Type 316CB 49
 - Type 316L 48
 - Type 321 51
 - Type 347 52
- Type 18 Cr - 8 Ni
 - hardness at elevated temperatures 387-390
 - relationship to strength and creep 391-393
- Type 347
 - elastic constants determined 848-852
- Type 431 + Mo alloy
 - hardness vs. aging time 98-99
 - hardness vs. hardening temperature 97-98
 - microstructure 98-99

Steel

- carburizing
 - effect of boron on case hardenability. See Carburizing steels, alloy.
 - effect of silicon on tempering. See under Silicon.
- flow stress 250-251
 - effect of mean distance between particles on .250-251
- plain carbon
 - hardness at elevated temperatures 390-391
 - relationship to strength and creep 391-393
- residual stress in
 - stress measurements of austenitic phase ... 657-661
 - effect of electrolytic polishing 657, 659
 - effect of stressing beyond the yield strength.. 658-660
 - stress measurements of martensitic phase 654-658, 660

Steel (cont.)

- residual stress in
 - stress measurements of martensitic phase
 - effect of cold work on .655-657
 - effect of electrolytic polishing on 657-658
 - effect of stressing beyond yield strength on .. 658-660
 - X-ray measurement of .638-676
 - decrease in the biaxial stress sum as a function of the applied bending stress 670-672
 - diffraction pattern obtained using various radiations 645-646
 - effect of specimen orientation on line symmetry 646-647
 - experimental necessities for determining ... 642-644
 - principles 639-642
 - technique 644-653
 - variation of "d" value with orientation of specimens 652-653
 - variation in relative intensity with 2θ .. 647-651
 - correction factors to compensate for intensity variation. 647-651, 661-666
- strain aging of sheet 344-361

Steel, alloy

- 8 Cr - 1 Mo type
 - hardness at elevated temperatures 390-393

Steel, eutectoid

- tensile properties
 - influence of structure on .252-253

Steel, trade designations

- AISI B-1112 and B-1113 alloys
 - effect of inclusions on machinability. See under Free machining steel.
- SAE 3140
 - impact energy curves
 - effect of hardness on .732-740

Steel, trade designations (cont.)

- SAE 3140 temper brittleness
 - effect of various heat treatments on. See under Temper brittleness.
- SAE 5140
 - endurance limit710-724

Strain aging

- of commercial sheet steels
 - accelerated test 351
 - in predicting age hardening352-354
 - in predicting yield point behavior354-357
- factors affecting rimmed steel346-350
- factors affecting stabilized steel350-351
- natural aging344-346

Strain hardening index

- correlation with deformation stress252-253

Stress concentration factor

- of temper-brittle steel ...719-721

Stress-rupture properties

- monel152-159, 164-170
 - graphical method of extrapolating and interpolating short-time data167-169
- stress vs. minimum creep rate
 - effect of cold work ..166-167
 - effect of testing temperature166-167
- stress vs. rupture life ..
 - 152-159, 164-165, 167
 - effect of cold work..
 - 153-159, 164-165, 167
 - effect of testing temperature ..153-154, 156-157, 164-165, 167-170
- of nodular iron at 1200 °F.368-373

Stress-strain relations

- for biaxially stressed 14S-T6. See Biaxial tensile stresses.

Sulphur

- effect on machinability of free machining steel .749-750

Sulphur (cont.)

- effect on properties of molybdenum alloys286-313

Surface-tension equilibrium

- in polyphase alloys541-545

Tantalum

- furnace for melting862-871

Technical Program and Reports of Officers, ASM—34th Annual Convention, Philadelphia, October 18 to 24, 1952 1

Temper brittleness

- effect of various heat treatments of SAE 3140 on heat treatments tested .726-727
- impact test results726-730
- transition curves727-730
- of SAE 3140 steel
 - effect of hardness on impact energy curves732-740

Temper-brittle steel

- endurance limit of
 - SAE 5140710-724
- heat treatments used ..712-714
- impact properties
 - 714-715, 717-719
- notch sensitivity factor .718
- stress concentration factor719-721
- tensile properties ..715, 717-719

Tempering

- first-stage kinetics582-590
- length changes on tempering583-588
- effect of carbon content583-588
- rate equation585, 587-590
- values of m for 589
- values of rate constant K589-590
- first-stage products of decomposition578-582
- ϵ -iron carbide578, 581, 585, 587-588, 590-591
- formula 587

Tempering (cont.)

- of high speed steel 18-4-1
 - effect of time and temperature on hardness .483-486, 488-490
 - on impact strength ..486-491
- low carbon martensitic phase
 - 578-579, 581-582
- carbon content of579, 582
- effect of tempering
 - temperature on ... 582
- of martensite
 - effect of silicon on. See under Silicon.
- mechanism and kinetics of the
 - first stage576-595
- model591-594
 - carbon concentration gradients at advancing front
 - 592-593
 - plane-front growth of aggregate at expense of primary martensite 592
 - rate constant K592-594
 - composition dependence 594
 - temperature dependence592-594
- second stage of595-597
 - activation energies for..595-597
 - variation with carbon content596-597
 - length changes from decomposition of austenite..595-596

Tempering temperature

- of steels containing silicon
 - effect on properties521-523

Tensile properties

- aluminum-copper alloys ..249-270
 - effect of dispersions on.249-270
 - method of determining
 - 254-262
- eutectoid steel252-253
 - influence of structure on.252-253
- forgings, SAE 10401096-1099
 - longitudinal1098-1099
 - effect of cooling rate
 - 1098-1099
 - transverse1097-1098
 - effect of cooling rate
 - 1097-1098

Tensile properties (cont.)

- forging steel, SAE 1045.1086-1116
 - correlation coefficients
 - 1086-1087, 1092, 1103
 - effect of angle of test on
 - .. 1099-1101, 1108, 1110-1111
 - elongation vs. angle of test 1108
 - reduction of area vs. angle of test 1108
 - effect of homogenization treatments on 1088-1089, 1094-1096
 - quenched and tempered specimens1101-1113
 - effect of angle of test on1108, 1110-1111
 - effect of reduction by forging 1101
 - reduction of area frequency curves1085-1086, 1094, 1096, 1115-1116
 - furnace-cooled specimens 1085
 - homogenized specimens1094, 1096
 - quenched and tempered specimens 1086
 - reduction of area vs. reduction by forging1088-1089, 1092-1096, 1103-1107, 1110
 - effect of homogenization treatment on 1088-1089, 1094-1096
 - effect of tempering temperature ...1103, 1105-1106
 - regression lines 1086-1087, 1092, 1103-1104, 1106-1107, 1109-1110
 - tensile strength vs. longitudinal reduction of area1103-1104, 1107
 - yield strength vs. longitudinal reduction of area1103-1104, 1106
 - yield strength vs. transverse reduction of area1103-1104, 1107

Tensile properties (cont.)

- forging steel, SAE 1045
 - specimens containing ferrite and pearlite 1088-1096, 1099-1101
- of temper-brittle steel SAE 5140715, 717-719

Test

- for strain aging of steel ..351-357

Thallium

- hardness
 - log hardness vs. temperature228, 232
 - showing allotropic transformation228, 232

Thorium

- effect on properties of molybdenum alloys286-313
- effect on recrystallization of molybdenum alloys314-332
- elastic constants determined850-852
- furnace for melting862-871

Tin

- effect on properties of molybdenum alloys286-313
- hardness
 - log hardness vs. temperature 230

Titanium

- elastic constants determined850-852, 855-857
- furnace for melting862-871
- hardness235-236
 - effect of impurities on ..235-236
- Lüders bands in tensile specimens988-990
- machinability957-965
 - effect of arsenic on.957, 961-962
 - effect of beryllium on .. 957, 959, 963
 - effect of boron on 957-958, 961-962
 - effect of carbon on 957-958, 962-963
 - effect of germanium on957, 961, 963

Titanium (cont.)

- machinability
 - effect of phosphorus on957, 961-962
 - effect of selenium on ... 957, 960, 962
 - effect of silicon on 957, 959, 962-963
 - effect of sulphur on 957, 959-960, 962-963
 - effect of tellurium on ... 957, 960-962
- high purity iodide vs. magnesium-reduced titanium957-960
- mechanical properties 949-953, 972-992
 - dependence of elastic modulus on temperature 981
 - dependence of elongation on temperature979-981
 - effect of strain rate on979-981
 - dependence of fracture stress on temperature978-980
 - effect of strain rate on978, 980
 - dependence of reduction of area on temperature980-981
 - effect of strain rate on980-981
 - dependence of yield strength on temperature977-979
 - effect of strain rate on977, 979
 - dependence of ultimate strength on temperature 978
 - effect of strain rate on 978
 - effect of arsenic on 950
 - effect of beryllium on .. 949
 - effect of boron on 949
 - effect of carbon on 949
 - effect of germanium on. 950
 - effect of phosphorus on. 950
 - effect of selenium on ... 950
 - effect of silicon on950-953
 - effect of sulphur on949-950
 - effect of tellurium on .. 950

Titanium (cont.)

- mechanical properties
 - fracture appearance at
 - different temperatures
 - of testing985, 987-988
 - plastic portion of true stress-strain curve981-983
 - strain aging effects972-992
 - yield point phenomenon.983-984
- stress-strain diagrams ...
 -975-977, 983-986
- effect of aging temperature
 - on984-986
- effect of increasing strain
 - on the appearance of a yield point following aging985-986
- effect of a prestrain at
 - liquid nitrogen on983-984
- effect of strain rate on..975, 977
- effect of testing temperature on975-977

Titanium alloys

- coefficients of expansion at
 - various temperatures.1001-1003
- fatigue properties..998-1001, 1003
 - at low temperatures ...
 -998-1001, 1003
 - effect of notch on ...998-1000
 - typical fractures ...1001, 1003
- hardness1000-1001
 - at low temperatures ..1000-1001
- impact strength
 -1000-1001, 1003-1004
 - at low temperatures ..1000-1001
 - typical fractures ...1003-1004
- machinability941-971
 - effect of saw wear on cutting
 - time 948
 - comparison with Type 304
 - stainless steel 948
 - effect of test variables..955-956
 - feed vs. load955-956
 - influence of insoluble
 - phases941-971
 - lathe test944-947, 954-962
 - method of evaluating.946-947
 - profilometer measurements 954

Titanium alloys (cont.)

- machinability
 - saw rating vs. turning index
 - for various titanium alloys962-964
 - correlation with Vickers
 - hardness and ultimate strength963-964
 - saw test
 -947-949, 957-964, 968-969
- mechanical properties
 - at low temperatures ..993-1007
 - effect on notch sensitivity
 -996-997
 - effect of testing temperature on995-997
- microstructure951-953
 - titanium - 0.67% arsenic
 -951, 953
 - titanium - 0.02% beryllium
 -952-953
 - titanium - 0.57% boron .951, 953
 - titanium - 0.47% carbon 951, 953
 - titanium - 0.25% germanium
 -952-953
 - titanium - 0.39% phosphorus
 -952-953
 - titanium - 0.99% selenium
 -952-953
 - titanium - 0.25% silver .951, 953
 - titanium - 0.32% sulphur
 - as Ti_3S_4 951, 953
 - titanium - 0.118% sulphur
 - as MoS_2 951, 953
 - titanium - 0.47% tellurium
 -952-953
 - titanium, unalloyed952-953

Titanium binary alloys

- martensite transformation
 - temperature934-939
- concentration vs. transformation temperature 935-939
 - titanium-chromium ..936-939
 - titanium-columbium
 -936, 938-939
 - titanium-iron935-939
 - titanium-manganese .936-938
 - titanium-molybdenum
 -935-936, 938-939

Titanium binary alloys (cont.)

- martensite transformation temp.
concentration vs. trans. temp.
titanium-tantalum ...
.....936, 938-939
- titanium-tungsten ...936, 938
- titanium-vanadium ..
.....935-936, 938-939

Titanium-oxygen

- phase diagram1012-1014

Titanium-oxygen alloys

- hardness1023-1024
- microstructures1012-1019

Titanium-oxygen system 1008-1028

- annealing treatments ..1010-1011
- appearance of ingots..1010-1011
- melting-range determinations
.....1019-1020
- melting temperatures .. 1020
- preparation of alloys ...1010-1012
- X-ray diffraction studies of
.....1020-1022
- alpha solid solution ..1020-1021
- lattice parameter-
composition curves 1021
- intermediate phase between
alpha and TiO ...1022-1023
- delta phase1022-1023
- intermediate phase TiO
.....1021-1022
- lattice parameter-
composition curves 1022

Tool steel

- residual stresses in605-617
- curvatures induced in
specimens607-609
- by etching607-609
- by lapping608-609
- effect of etching on
.....607-609, 614-615
- effect of grinding on ...
.....609, 614-615
- effect of lapping on
.....608-609, 614-615
- effect of quenching and
tempering on605-615
- effect of tempering on
surface stress612-614, 617

Tool steel (cont.)

- residual stresses in
stress distribution611-613
- equation for determining 611

Transition temperatures

- of SAE 3140 steel
after various heat treat-
ments727-730

Treasurer's Annual Report.. 10**Tungsten**

- effect on properties of
molybdenum alloys286-313
- effect on recrystallization of
molybdenum alloys314-332

Tungsten-chromium-vanadium steel

- high speed steel 18-4-1. See
under High speed steel.

Ultrasonics

- use in determining elastic
constants
apparatus and experimental
technique845-849
- of beryllium ...850-852, 855-857
- of brass847-848, 850-852
- of columbium850-852
- elastic constant equations 845
- of molybdenum855-857
- possible reasons for dis-
crepancies856-859
- of thorium850-852
- of titanium850-852, 855-857
- of Type 347 stainless steel
.....848-852
- types of elastic waves prop-
agated in solids ...839-840
- wave reflections at bound-
aries840-841
- of uranium850-852
- of vanadium850-852
- wave propagation between
parallel faces of solids 841-842
- wave propagation in cylin-
drical rods842-844
- measurement of wave
velocities844-845
- of zirconium ...850-852, 855-857

Uranium

- elastic constants determined
.....850-852
- furnace for melting862-871

Vanadium

- in carburizing steels
 - effect with boron on case
hardness778, 783
- elastic constants determined
.....850-852
- in high speed steel 18-4-1
 - effect on hardness
.....480-481, 484

Vanadium rimmed steel

- strain aging characteristics
.....344-361

X-ray diffraction study

- of austenite and sigma
separated from Cr-Ni-Mo-Ti
(18-8-3-1) alloy 445
- of microconstituents in high
temperature alloys397-428
- of rolled low carbon steel
 - effect of rolling temperature
on texture333-343
- of steels containing silicon
 - effect of silicon during
tempering516-520

Yield strength

- of 14S-T6 stressed biaxially
agreement with distortion
energy theory 692

Young's modulus

- See Modulus of elasticity.

Zinc

- hardness
 - log hardness vs. temper-
ature 228

Zinc-copper alloy

- discontinuous precipitation in
.....564-565

Zirconium

- arc melting furnace for
 - advantages 870
 - applicability to other
metals869-870
 - design of furnace864-866
 - operation of furnace ...865-869
 - pressed zirconium electrodes
used863-864
- elastic constants determined
.....850-852, 855-857
- properties of high purity
zirconium. See Zirconium-
oxygen alloys.

Zirconium-nickel system

- microstructures897-899
- phase diagram, partial ... 895

Zirconium-oxygen alloys

- effect of oxygen on hardness
.....881-882
- effect of oxygen on recrystal-
lization 884
- effect of oxygen on resistivity
.....879-881
- effect of oxygen on tensile
properties882-883
- effect of oxygen on thermal
conductivity 881
- elevated temperature tensile
properties885-889
- hydrogen content of zirconium
.....876-877
- microstructure883-884
- oxygen diffusion rate in
zirconium884-885
- preparation of alloys877-878
- stress-strain curves at various
temperatures886, 888-889
- table of physical and
mechanical properties .. 880
- workability883-884

Zirconium-silicon system

- microstructures906-912
- phase diagram903-905

Zirconium-tin system

- microstructures921-927
- phase diagram918-919

